

EN _____ The Indox range of truly trimless downlights is a great example of timeless, cutting edge design. The Indox is designed for a full range of glare reducing, deep-set lamp units, and is ideal for energy efficient LED lamps. A unique mounting system allows you to rotate the lamp in all directions with a single, almost invisible ring. The fully paintable Indox series creates an unobtrusive luminaire in perfect harmony with the architecture. The Indox range is ideal for a wide range of lighting applications: residential buildings, shops, offices, meeting rooms, hotels, etc. The time-less Indox range is a perfect match for contemporary and classical interiors.



DE _____ Die Indox-Reihe von komplett randlosen Deckenleuchten ist ein großartiges Beispiel für zeitloses, hochaktuelles Design. Indox bietet ein vollständiges Sortiment an blendungsreduzierenden, tief liegenden Lampeneinheiten und eignet sich ideal für energiesparende LED-Lampen. Dank des einzigartigen Montagesystems lässt sich die Lampe mit einem einzigen, fast unsichtbaren Ring in alle Richtungen drehen. Die vollständig anstrichfähige Indox-Reihe bietet eine dezente Leuchte, die sich perfekt in jede Inneneinrichtung einfügt. Die Indox-Reihe eignet sich ideal für ein breites Spektrum an Beleuchtungsanwendungen: Wohnbauten, Geschäfte, Büros, Konferenzräume, Hotels usw. Die zeitlose Indox-Reihe fügt sich perfekt in sowohl moderne als auch klassische Inneneinrichtungen.

FR _____ La collection de plafonniers sans cadre Indox est l'exemple même d'un design ultramoderne et intemporel. Indox est conçu pour un large éventail de lampes encastrées à faible éblouissement et convient parfaitement aux lampes à LED écoénergétiques. Un système unique vous permet de faire pivoter la lampe dans tous les sens, à l'aide d'un anneau quasi invisible. Les luminaires à peindre Indox créent un éclairage discret, en parfaite harmonie avec votre architecture. La collection Indox s'adapte à de nombreuses applications d'éclairage : bâtiments résidentiels, boutiques, bureaux, salles de réunion, hôtels, etc. Cette gamme indémodable se marie très bien avec les décorations contemporaines et classiques.

IT _____ La gamma Indox presenta elementi dal design innovativo e senza tempo. Gli elementi della serie Indox sono stati sviluppati per donare un'ampia gamma di luminosità, fattore questo che riduce il numero di punti luce. Sono ideali per le lampade al LED ad efficienza energetica. Il particolare sistema di montaggio permette di ruotare la lampada in tutte le direzioni grazie ad un unico anello invisibile. La serie Indox è completamente verniciabile e crea un punto luce non ostruttivo in perfetta armonia con l'architettura dell'ambiente circostante. La gamma Indox è ideale per un'ampia gamma di applicazioni: edifici residenziali, negozi, uffici, sale riunioni, hotel etc. La gamma evergreen Indox è indicata con gli arredamenti moderni che classici.

NL _____ De randloze downlights van de Indox-reeks zijn een prachtig voorbeeld van tijdloos en geavanceerd design. Indox werd ontworpen als gamma met diepliggende verlichtingsbronnen voor een zachtere gloed en is ideaal voor energiezuinige leds. Dankzij het unieke montagesysteem roteert u de lamp in alle richtingen aan de hand van een bijna onzichtbare ring. De volledig overschilderbare Indox-reeks staat voor een onopvallende armatuur die perfect harmonieert met de architectuur. Het Indox-gamma is geschikt voor een breed aantal toepassingen: woningen, winkels, kantoren, vergaderzalen, hotels, enz. De tijdloze Indox-reeks vormt een perfecte match met zowel moderne als klassieke interieurs.

ES _____ La gama de Indox de iluminación hacia abajo verdaderamente sin cortes es un gran ejemplo de diseño de vanguardia atemporal. El Indox está diseñado para una amplia gama de unidades de luces hundidas con reducción de reflejos, y es ideal para la iluminación de LED de energía eficiente. Un exclusivo sistema de montaje permite girar la lámpara en todas las direcciones con un solo anillo, casi invisible. La serie Indox totalmente pintable crea una luminaria discreta en perfecta armonía con la arquitectura. La gama Indox es ideal para una amplia gama de aplicaciones de iluminación: edificios de viviendas, tiendas, oficinas, salas, hoteles, etc. La gama Indox atemporal es una combinación perfecta para los interiores contemporáneos y clásicos.




INDOX 30 IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable ϕ 0° - 10°

114x134 mm

Material: CALCYT® plaster




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 274 99 025 installation system for gypsum ceiling 25 mm

REF N° 274 99 030 installation system for gypsum ceiling 30 mm

REF N° 843 00 000 Concrete box Indox 30/50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 32°

REF N° 204 30 024 optional beam angle 24°

REF N° 204 30 040 optional beam angle 40°

REF N° 204 30 050 optional beam angle 50°

REMOTE LED DRIVER DIM 250mA/350mA

REF N° 697 60 040 DIM 1-10V DALI PUSH 30W

REF N° 697 60 150 DIM 1-10V 100W

REF N° 697 30 150 DIM DALI 100W

INDOX 30 LED 450LM CRI 97 230VAC

REF N° 274 71 930 phase DIM CRI 97 2700°K

REF N° 274 71 830 phase DIM CRI 97 3000°K

6,5W - 450lm - 2 Step MacAdam $\square$ 230V/50Hz
Standard beam angle 32° (options 40°, 50°)
Parallel wiring - Connects directly to 230VAC
h=98 - CE - ∇ - A - P

INDOX 30 LED 450LM CRI 97 REMOTE DRIVER

REF N° 274 29 930 excl. LED driver CRI 97 2700°K

REF N° 274 29 830 excl. LED driver CRI 97 3000°K

6,5W - 450lm - 2 Step MacAdam
Standard beam angle 32° (options 40°, 50°)
Serial wiring - Requires remote LED driver
h=98 - CE - ∇ - A - P

INDOX 30 LED 600LM 230VAC

REF N° 274 71 530 phase DIM CRI 80 2200°K

REF N° 274 71 030 phase DIM CRI 90 2700°K

REF N° 274 71 130 phase DIM CRI 90 3000°K

6,5W - 600lm - 2 Step MacAdam $\square$ 230V/50Hz
Standard beam angle 32° (options 24°, 40°, 50°)
Parallel wiring - Connects directly to 230VAC
h=98 - CE - ∇ - A - P

INDOX 30 LED 600LM REMOTE DRIVER

REF N° 274 29 530 excl. LED driver CRI 80 2200°K

REF N° 274 29 030 excl. LED driver CRI 90 2700°K

REF N° 274 29 130 excl. LED driver CRI 90 3000°K

6,5W - 600lm - 2 Step MacAdam
Standard beam angle 32° (options 24°, 40°, 50°)
Serial wiring - Requires remote LED driver
h=98 - CE - ∇ - A - P

INDOX 30 LED 200LM REAL SPOT 230VAC

REF N° 274 70 510 phase DIM CRI 80 2200°K

REF N° 274 70 010 phase DIM CRI 90 2700°K

REF N° 274 70 110 phase DIM CRI 90 3000°K

3W - 200lm - 3 Step MacAdam $\square$ 230V/50Hz
5° beam angle - CE - ∇ - A - P
Parallel wiring - Connects directly to 230VAC
h=98

INDOX 30 LED 200LM REAL SPOT REMOTE DRIVER

REF N° 274 29 510 excl. LED driver CRI 80 2200°K

REF N° 274 29 010 excl. LED driver CRI 90 2700°K

REF N° 274 29 110 excl. LED driver CRI 90 3000°K

3W - 200lm - 3 Step MacAdam
5° beam angle - CE - ∇ - A - P
Serial wiring - Requires remote LED driver
h=98




INDOX 30 IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Adjustable $\odot$ 0° - 10°

114x134 mm

Material: CALCYT® plaster




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 274 99 025 installation system for gypsum ceiling 25 mm

REF N° 274 99 030 installation system for gypsum ceiling 30 mm

REF N° 843 00 000 Concrete box Indox 30/50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 32°

REF N° 204 30 024 optional beam angle 24°

REF N° 204 30 040 optional beam angle 40°

REF N° 204 30 050 optional beam angle 50°

REMOTE LED DRIVER DIM 250mA/350mA

REF N° 697 60 040 DIM 1-10V DALI PUSH 30W

REF N° 697 60 150 DIM 1-10V 100W

REF N° 697 30 150 DIM DALI 100W

INDOX 30 LED 450LM CRI 97 230VAC

REF N° 274 71 931 phase DIM CRI 97 2700°K

REF N° 274 71 831 phase DIM CRI 97 3000°K

6,5W - 450lm - 2 Step MacAdam $\square$ 230V/50Hz
Standard beam angle 32° (options 40°, 50°)
Parallel wiring - Connects directly to 230VAC
h=98 - CE - A - P

INDOX 30 LED 450LM CRI 97 REMOTE DRIVER

REF N° 274 29 931 excl. LED driver CRI 97 2700°K

REF N° 274 29 831 excl. LED driver CRI 97 3000°K

6,5W - 450lm - 2 Step MacAdam
Standard beam angle 32° (options 40°, 50°)
Serial wiring - Requires remote LED driver
h=98 - CE - A - P

INDOX 30 LED 600LM 230VAC

REF N° 274 71 531 phase DIM CRI 80 2200°K

REF N° 274 71 031 phase DIM CRI 90 2700°K

REF N° 274 71 131 phase DIM CRI 90 3000°K

6,5W - 600lm - 2 Step MacAdam $\square$ 230V/50Hz
Standard beam angle 32° (options 24°, 40°, 50°)
Parallel wiring - Connects directly to 230VAC
h=98 - CE - A - P

INDOX 30 LED 600LM REMOTE DRIVER

REF N° 274 29 531 excl. LED driver CRI 80 2200°K

REF N° 274 29 031 excl. LED driver CRI 90 2700°K

REF N° 274 29 131 excl. LED driver CRI 90 3000°K

6,5W - 600lm - 2 Step MacAdam
Standard beam angle 32° (options 24°, 40°, 50°)
Serial wiring - Requires remote LED driver
h=98 - CE - A - P




INDOX 30 IP54

OUTDOOR - ESTERNO - AUßENBEREICH - EXTERIEUR - EXTÉRIEUR - EXTERIOR

Adjustable ϕ 0° - 10°

114x134 mm

Material : waterproof CALCYT+®




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 274 99 025 installation system for gypsum ceiling 25 mm

REF N° 274 99 030 installation system for gypsum ceiling 30 mm

REF N° 843 00 000 Concrete box Indox 30/50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 32°

REF N° 204 30 024 optional beam angle 24°

REF N° 204 30 040 optional beam angle 40°

REF N° 204 30 050 optional beam angle 50°

REMOTE LED DRIVER DIM 250mA/350mA

REF N° 697 60 040 DIM 1-10V DALI PUSH 30W

REF N° 697 60 150 DIM 1-10V 100W

REF N° 697 30 150 DIM DALI 100W

INDOX 30 LED 450LM CRI 97 230VAC

REF N° 274 71 935 phase DIM CRI 97 2700°K

REF N° 274 71 835 phase DIM CRI 97 3000°K

6,5W - 450lm - 2 Step MacAdam $\square$ 230V/50Hz
Standard beam angle 32° (options 40°, 50°)
Parallel wiring - Connects directly to 230VAC
h=98 - - - -

INDOX 30 LED 450LM CRI 97 REMOTE DRIVER

REF N° 274 29 935 excl. LED driver CRI 97 2700°K

REF N° 274 29 835 excl. LED driver CRI 97 3000°K

6,5W - 450lm - 2 Step MacAdam
Standard beam angle 32° (options 40°, 50°)
Serial wiring - Requires remote LED driver
h=98 - - - -

INDOX 30 LED 600LM 230VAC

REF N° 274 71 535 phase DIM CRI 80 2200°K

REF N° 274 71 035 phase DIM CRI 90 2700°K

REF N° 274 71 135 phase DIM CRI 90 3000°K

6,5W - 600lm - 2 Step MacAdam $\square$ 230V/50Hz
Standard beam angle 32° (options 24°, 40°, 50°)
Parallel wiring - Connects directly to 230VAC
h=98 - - - -

INDOX 30 LED 600LM REMOTE DRIVER

REF N° 274 29 535 excl. LED driver CRI 80 2200°K

REF N° 274 29 035 excl. LED driver CRI 90 2700°K

REF N° 274 29 135 excl. LED driver CRI 90 3000°K

6,5W - 600lm - 2 Step MacAdam
Standard beam angle 32° (options 24°, 40°, 50°)
Serial wiring - Requires remote LED driver
h=98 - - - -




INDOX 50 MINI IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable Φ 0° - 30°

114x144 mm

Material: CALCYT® plaster




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 221 99 025 installation system for gypsum ceiling 25 mm

REF N° 221 99 030 installation system for gypsum ceiling 30 mm

REF N° 834 00 000 Concrete box Indox 50 mini - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI

INDOX 50 MINI LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80	900LM CRI90
phase DIM	221 72 640	221 73 640
DIM 1-10V	221 62 640	221 63 640
DIM DALI	221 32 640	221 33 640

6W (500lm) - 12,8W (900lm) - 4 Step MacAdam
 $\square$ - 230V/50Hz - CE - ∇ - A - B
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 24°)
 h = 115 mm (500lm) - h = 150 mm (900lm)

INDOX 50 MINI LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	221 73 040	221 73 140	221 73 240
DIM 1-10V	221 63 040	221 63 140	221 63 240
DIM DALI	221 33 040	221 33 140	221 33 240

Xicato LED - 11,7W - 1300lm - 2 Step MacAdam
 $\square$ - 230V/50Hz - CE - ∇ - A - A
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 150 mm

INDOX 50 MINI LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	221 72 040	221 72 140	221 72 240
DIM 1-10V	221 62 040	221 62 140	221 62 240
DIM DALI	221 32 040	221 32 140	221 32 240

Xicato LED - 5,6 W - 720lm - 2 Step MacAdam
 $\square$ - 230V/50Hz - CE - ∇ - A - A
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 92 mm (phase DIM models beam 36°)
 h = 115 mm (all other models)

INDOX 50 MINI LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	221 72 940	221 72 840	221 72 740
DIM 1-10V	221 62 940	221 62 840	221 62 740
DIM DALI	221 32 940	221 32 840	221 32 740

Xicato LED - 7,4 W - 720lm - 2 Step MacAdam
 $\square$ - 230V/50Hz - CE - ∇ - A - A
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 115 mm (models beam angle 36°)
 h = 150 mm (models beam angle 12° or 24°)

INDOX 50 MINI HAL

REF N° 221 10 050

QR-CBC 51 - 50W - Gx5.3 - 12V
 CE - ∇ - A - D
 h = 92 mm - exclusive lamp and transfo

INDOX 50 MINI ES

REF N° 221 11 050

QPAR 16 - 50W - GZ10/GU10 - A
 CE - 230V/50Hz - ∇ - A - D
 h = 93 mm - exclusive lamp

INDOX 50 MINI IP20

ACCESSORIES - ACCESSORI - ZUBEHÖR - ACCESSOIRES - ACCESORIOS



STANDARD (included) LAMPHOLDER RING WHITE



REF N° 201 10 002 LAMPHOLDER RING BLACK



REF N° 201 11 001
EXTENSION S WHITE
Ø 56 x 26 mm Φ 0° - 10°



REF N° 201 12 001
EXTENSION M WHITE
Ø 56 x 36 mm Φ 0° - 10°



REF N° 201 13 001
EXTENSION L WHITE
Ø 56 x 68 mm Φ 0° - 10°



REF N° 201 11 002
EXTENSION S BLACK
Ø 56 x 26 mm Φ 0° - 10°



REF N° 201 12 002
EXTENSION M BLACK
Ø 56 x 36 mm Φ 0° - 10°



REF N° 201 13 002
EXTENSION L BLACK
Ø 56 x 68 mm Φ 0° - 10°



REF N° 201 51 001
FROSTED PLEXI WHITE
Only for LED lampsources




REF N° 201 52 001
HONEYCOMB WHITE
Only for LED lampsources



REF N° 201 53 001
SPHERICAL GLASS LENS
IN WHITE RING



REF N° 201 51 002
FROSTED PLEXI BLACK
Only for LED lampsources



REF N° 201 52 002
HONEYCOMB BLACK
Only for LED lampsources



REF N° 201 53 002
SPHERICAL GLASS LENS
IN BLACK RING





INDOX 50 MINI IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

114x144 mm

Material : CALCYT® plaster

INDOX 50 MINI LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80	900LM CRI90
phase DIM	221 72 641	221 73 641
DIM 1-10V	221 62 641	221 63 641
DIM DALI	221 32 641	221 33 641

6 W (500lm) - 12,8 W (900lm) - 4 Step MacAdam
 - 230V/50Hz -  -  -  - 
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 24°)
 h = 115 mm (500lm) - h = 150 mm (900lm)

INDOX 50 MINI LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	221 73 041	221 73 141	221 73 241
DIM 1-10V	221 63 041	221 63 141	221 63 241
DIM DALI	221 33 041	221 33 141	221 33 241

Xicato LED - 11,7 W - 1300lm - 2 Step MacAdam
 - 230V/50Hz -  -  -  - 
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 150 mm

INDOX 50 MINI LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	221 72 041	221 72 141	221 72 241
DIM 1-10V	221 62 041	221 62 141	221 62 241
DIM DALI	221 32 041	221 32 141	221 32 241

Xicato LED - 5,6 W - 720lm - 2 Step MacAdam
 - 230V/50Hz -  -  -  - 
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 92 mm (phase DIM models beam 36°)
 h = 115 mm (all other models)

INDOX 50 MINI LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	221 72 941	221 72 841	221 72 741
DIM 1-10V	221 62 941	221 62 841	221 62 741
DIM DALI	221 32 941	221 32 841	221 32 741

Xicato LED - 7,4 W - 720lm - 2 Step MacAdam
 - 230V/50Hz -  -  -  - 
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 115 mm (models beam angle 36°)
 h = 150 mm (models beam angle 12° or 24°)

INDOX 50 MINI HAL


REF N° 221 10 051

 QR-CBC 51 - 50W - Gx5.3 - 12V
 -  -  -  -  - 
 h = 92 mm - exclusive lamp and transfo

INDOX 50 MINI ES

REF N° 221 11 051

 QPAR 16 - 50W - GZ10/GU10 - 
 -  - 230V/50Hz -  -  -  - 
 h = 93 mm - exclusive lamp




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 221 99 025 installation system for gypsum ceiling 25 mm

REF N° 221 99 030 installation system for gypsum ceiling 30 mm

REF N° 834 00 000 Concrete box Indox 50 mini - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI




INDOX 50 MINI IP54

OUTDOOR - ESTERNO - AUßENBEREICH - EXTERIEUR - EXTERIOR

Fix (not adjustable) 0° - 0°

114x144 mm

Material : waterproof CALCYT+*




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 221 99 025 installation system for gypsum ceiling 25 mm

REF N° 221 99 030 installation system for gypsum ceiling 30 mm

REF N° 834 00 000 Concrete box Indox 50 mini - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI

INDOX 50 MINI LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80	900LM CRI90
phase DIM	221 72 645	221 73 645
DIM 1-10V	221 62 645	221 63 645
DIM DALI	221 32 645	221 33 645

6 W (500lm) - 12,8 W (900lm) - 4 Step MacAdam

☐ - 230V/50Hz - CE - ▽ - ⚡ - B

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 24°)

h = 115 mm (500lm) - h = 150 mm (900lm)

INDOX 50 MINI LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	221 73 045	221 73 145	221 73 245
DIM 1-10V	221 63 045	221 63 145	221 63 245
DIM DALI	221 33 045	221 33 145	221 33 245

Xicato LED - 11,7 W - 1300lm - 2 Step MacAdam

☐ - 230V/50Hz - CE - ▽ - ⚡ - A

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 150 mm

INDOX 50 MINI LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	221 72 045	221 72 145	221 72 245
DIM 1-10V	221 62 045	221 62 145	221 62 245
DIM DALI	221 32 045	221 32 145	221 32 245

Xicato LED - 5,6 W - 720lm - 2 Step MacAdam

☐ - 230V/50Hz - CE - ▽ - ⚡ - A+

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 92 mm (phase DIM models beam 36°)

h = 115 mm (all other models)

INDOX 50 MINI LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	221 72 945	221 72 845	221 72 745
DIM 1-10V	221 62 945	221 62 845	221 62 745
DIM DALI	221 32 945	221 32 845	221 32 745

Xicato LED - 7,4 W - 720lm - 2 Step MacAdam

☐ - 230V/50Hz - CE - ▽ - ⚡ - A

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 115 mm (models beam angle 36°)

h = 150 mm (models beam angle 12° or 24°)

INDOX 50 MINI HAL

REF N° 221 10 055

☐ QR-CBC 51 - 50W - Gx5.3 - 12V

☐ - CE - ⚡ - ▽ - 0.5m - D

h = 92 mm - exclusive lamp and transfo

INDOX 50 MINI ES

REF N° 221 11 055

☐ QPAR 16 - 50W - GZ10/GU10 - ⚡

☐ - CE - 230V/50Hz - ▽ - 0.5m - D

h = 93 mm - exclusive lamp



INDOX R 50 IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable Φ 0° - 30°

Φ 120 mm

Material : CALCYT® plaster

INDOX R 50 LED 500LM CRI 80 REMOTE DRIVER WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N° 271 29 640

6 W - 500lm - 4 Step MacAdam

CE - ∇ - $\square$ - $\square$ - $\square$ - Excl. LED driver

Requires remote LED driver @ 350 mA

Standard beam angle 36° (options 24°)

h = 123 mm

INDOX R 50 LED 700LM CRI 80 REMOTE DRIVER

REF N° 271 29 040 2700K

REF N° 271 29 140 3000K

REF N° 271 29 240 4000K

Xicato LED - 5,6 W - 720lm - 2 Step MacAdam

CE - ∇ - $\square$ - $\square$ - $\square$ - Excl. LED driver

Requires remote LED driver @ 350 mA

Standard beam angle 36° (options 12°, 24°)

h = 123 mm

INDOX R 50 HAL

REF N° 271 10 050

$\square$ QR-CBC 51 - 50W - Gx5.3 - 12V

$\square$ - CE - $\square$ - $\square$ - $\square$ - $\square$ - 0.5m - $\square$

h = 123 mm - exclusive lamp and transfo

REMOTE LED DRIVER ON/OFF

REF N° 697 00 006 8W

REF N° 697 00 015 15W

REF N° 697 00 025 25W

230V/50Hz - $\square$ - current controlled

∇ - CE - IP20 - 350mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 006 6W 1-10V

REF N° 697 60 015 15W 1-10V

REF N° 697 30 015 15W DALI

REF N° 697 60 025 25W 1-10V DALI PUSH

REF N° 697 60 040 40W 1-10V DALI PUSH

REF N° 697 60 150 150W 1-10V

REF N° 697 30 150 150W DALI

REF N° 697 70 009 9W PHASE DIM (tr. edge)

REF N° 697 70 017 17W PHASE DIM

230V/50Hz - $\square$ - current controlled

∇ - CE - IP20 - 350mA - dimmable




INDOX R 50 ES

REF N° 271 11 050

$\square$ QPAR 16 - 50W - GZ10/GU10 - $\square$

$\square$ - CE - 230V/50Hz - ∇ - $\square$ - 0.5m - $\square$

h = 123 mm - exclusive lamp



INSTALLATION KIT

STANDARD (included) installation system for concrete ceiling
height adjustable

BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°



INDOX R 50 IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

Ø120 mm

Material : CALCYT® plaster

INDOX R 50 LED 500LM CRI 80 REMOTE DRIVER WARM DIM

WARM DIM : DIMS FROM 3000°K TO 2000°K

REF N° 271 29 641

6 W - 500lm - 4 Step MacAdam

CE - ∇ - A+ - Excl. LED driver

Requires remote LED driver @ 350 mA

Standard beam angle 36° (options 24°)

h = 123 mm

INDOX R 50 LED 700LM CRI 80 REMOTE DRIVER

REF N° 271 29 041 2700K

REF N° 271 29 141 3000K

REF N° 271 29 241 4000K

Xicato LED - 5,6W - 720lm - 2 Step MacAdam

CE - ∇ - A+ - Excl. LED driver

Requires remote LED driver @ 350 mA

Standard beam angle 36° (options 12°, 24°)

h = 123 mm

INDOX R 50 HAL

REF N° 271 10 051

QR-CBC 51 - 50W - Gx5.3 - 12V

CE - ∇ - A+ - Excl. LED driver

Standard beam angle 36° (options 12°, 24°)

h = 123 mm - exclusive lamp and transfo

INDOX R 50 ES

REF N° 271 11 051

QPAR 16 - 50W - GZ10/GU10 -

CE - ∇ - A+ - Excl. LED driver

Standard beam angle 36° (options 12°, 24°)

h = 123 mm - exclusive lamp

REMOTE LED DRIVER ON/OFF

REF N° 697 00 006 8W

REF N° 697 00 015 15W

REF N° 697 00 025 25W

230V/50Hz - - current controlled

∇ - CE - IP20 - 350mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 006 6W 1-10V

REF N° 697 60 015 15W 1-10V

REF N° 697 30 015 15W DALI

REF N° 697 60 025 25W 1-10V DALI PUSH

REF N° 697 60 040 40W 1-10V DALI PUSH

REF N° 697 60 150 150W 1-10V




REF N° 697 30 150 150W DALI

REF N° 697 70 009 9W PHASE DIM (tr. edge)

REF N° 697 70 017 17W PHASE DIM

230V/50Hz - - current controlled

∇ - CE - IP20 - 350mA - dimmable



INSTALLATION KIT

STANDARD (included) installation system for concrete ceiling
height adjustable

BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°



INDOX R 50 IP54

OUTDOOR - ESTERNO - AUßENBEREICH - EXTERIEUR - EXTÉRIEUR - EXTERIOR

Fix (not adjustable) 0° - 0°

Ø120 mm

Material : waterproof CALCYT+®

INDOX R 50 LED 500LM CRI 80 REMOTE DRIVER WARM DIM

WARM DIM : DIMS FROM 3000°K TO 2000°K

REF N° 271 29 645

6W - 500lm - 4 Step MacAdam

CE -  -  - Excl. LED driver

Requires remote LED driver @ 350 mA

Standard beam angle 36° (options 24°)

h = 123 mm

INDOX R 50 LED 700LM CRI 80 REMOTE DRIVER

REF N° 271 29 045 2700K

REF N° 271 29 145 3000K

REF N° 271 29 245 4000K

Xicato LED - 5,6W - 720lm - 2 Step MacAdam

CE -  -  - A+ - Excl. LED driver

Requires remote LED driver @ 350 mA

Standard beam angle 36° (options 12°, 24°)

h = 123 mm

INDOX R 50 HAL

REF N° 271 10 055

 QR-CBC 51 - 50W - Gx5.3 - 12V

 - CE -  -  -  - 0.5m - 

h = 123 mm - exclusive lamp and transfo

REMOTE LED DRIVER ON/OFF

REF N° 697 00 006 8W

REF N° 697 00 015 15W

REF N° 697 00 025 25W

230V/50Hz -  - current controlled

 - CE - IP20 - 350mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 006 6W 1-10V

REF N° 697 60 015 15W 1-10V

REF N° 697 30 015 15W DALI

REF N° 697 60 025 25W 1-10V DALI PUSH

REF N° 697 60 040 40W 1-10V DALI PUSH

REF N° 697 60 150 150W 1-10V

REF N° 697 30 150 150W DALI

REF N° 697 70 009 9W PHASE DIM (tr. edge)

REF N° 697 70 017 17W PHASE DIM

230V/50Hz -  - current controlled

 - CE - IP20 - 350mA - dimmable



INDOX R 50 ES

REF N° 271 11 055

 QPAR 16 - 50W - GZ10/GU10 - 

 - CE - 230V/50Hz -  - 0.5m - 

h = 123 mm - exclusive lamp



INSTALLATION KIT

STANDARD (included) installation system for concrete ceiling
height adjustable

BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°



INDOX 2X50 MINI IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable ϕ 0° - 30°

114x244 mm

Material: CALCYT® plaster

INDOX 2X50 MINI LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80
phase DIM	224 72 640
DIM 1-10V	224 62 640
DIM DALI	224 32 640

2x 6 W - 2x 500lm - 4 Step MacAdam

☐ - 230V/50Hz -  -  - 
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 24°)
h = 115 mm

INDOX 2X50 MINI LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	224 73 040	224 73 140	224 73 240
DIM 1-10V	224 63 040	224 63 140	224 63 240
DIM DALI	224 33 040	224 33 140	224 33 240

2x Xicato LED - 2x 11,7 W - 2x 1300lm

☐ - 230V/50Hz -  -  - 
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 150 mm

INDOX 2X50 MINI LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	224 72 040	224 72 140	224 72 240
DIM 1-10V	224 62 040	224 62 140	224 62 240
DIM DALI	224 32 040	224 32 140	224 32 240

2x Xicato LED - 2x 5,6 W - 2x 720lm

☐ - 230V/50Hz -  -  - 
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 92 mm (phase DIM models beam 36°)
h = 115 mm (all other models)

INDOX 2X50 MINI LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	224 72 940	224 72 840	224 72 740
DIM 1-10V	224 62 940	224 62 840	224 62 740
DIM DALI	224 32 940	224 32 840	224 32 740

2x Xicato LED - 2x 7,4 W - 2x 720lm

☐ - 230V/50Hz -  -  - 
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 115 mm (models beam angle 36°)
h = 150 mm (models beam angle 12° or 24°)

INDOX 2X50 MINI HAL


REF N° 224 10 050

☐ 2x QR-CBC 51 - 50W - Gx5.3 - 12V
 -  -  -  -  - 
h = 92 mm - exclusive lamp and transfo

INDOX 2X50 MINI ES

REF N° 224 11 050

☐ 2x QPAR 16 - 50W - GZ10/GU10 - 
 -  - 230V/50Hz -  -  - 
h = 93 mm - exclusive lamp



INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 224 99 025 installation system for gypsum ceiling 25 mm

REF N° 224 99 030 installation system for gypsum ceiling 30 mm

BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI

INDOX 2X50 MINI IP20

ACCESSORIES - ACCESSORI - ZUBEHÖR - ACCESSOIRES - ACCESORIOS



STANDARD (included) 2 x LAMPHOLDER RING WHITE



REF N° 201 10 022 2 x LAMPHOLDER RING BLACK



REF N° 201 11 001
1 x EXTENSION S WHITE
Ø 56 x 26 mm $\pm$ 0° - 10°



REF N° 201 12 001
1 x EXTENSION M WHITE
Ø 56 x 36 mm $\pm$ 0° - 10°



REF N° 201 13 001
1 x EXTENSION L WHITE
Ø 56 x 68 mm $\pm$ 0° - 10°



REF N° 201 11 002
1 x EXTENSION S BLACK
Ø 56 x 26 mm $\pm$ 0° - 10°



REF N° 201 12 002
1 x EXTENSION M BLACK
Ø 56 x 36 mm $\pm$ 0° - 10°



REF N° 201 13 002
1 x EXTENSION L BLACK
Ø 56 x 68 mm $\pm$ 0° - 10°



REF N° 201 51 001
1 x FROSTED PLEXI WHITE
Only for LED lampsources



REF N° 201 52 001
1 x HONEYCOMB WHITE
Only for LED lampsources



REF N° 201 53 001
1 x SPHERICAL GLASS LENS
IN WHITE RING



REF N° 201 51 002
1 x FROSTED PLEXI BLACK
Only for LED lampsources



REF N° 201 52 002
1 x HONEYCOMB BLACK
Only for LED lampsources



REF N° 201 53 002
1 x SPHERICAL GLASS LENS
IN BLACK RING

INDOX 2X50 MINI IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

114x244 mm

Material : CALCYT® plaster

INDOX 2X50 MINI LED WARM DIM

WARM DIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80
phase DIM	224 72 641
DIM 1-10V	224 62 641
DIM DALI	224 32 641

2x 6 W - 2x 500lm - 4 Step MacAdam

☐ - 230V/50Hz - ☑ - ☐ - ☐ - ☐
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 24°)
h = 115 mm

INDOX 2X50 MINI LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	224 73 041	224 73 141	224 73 241
DIM 1-10V	224 63 041	224 63 141	224 63 241
DIM DALI	224 33 041	224 33 141	224 33 241

2x Xicato LED - 2x 11,7 W - 2x 1300lm

☐ - 230V/50Hz - ☑ - ☐ - ☐ - ☐
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 150 mm

INDOX 2X50 MINI LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	224 72 041	224 72 141	224 72 241
DIM 1-10V	224 62 041	224 62 141	224 62 241
DIM DALI	224 32 041	224 32 141	224 32 241

2x Xicato LED - 2x 5,6 W - 2x 720lm

☐ - 230V/50Hz - ☑ - ☐ - ☐ - ☐
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 92 mm (phase DIM models beam 36°)
h = 115 mm (all other models)

INDOX 2X50 MINI LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	224 72 941	224 72 841	224 72 741
DIM 1-10V	224 62 941	224 62 841	224 62 741
DIM DALI	224 32 941	224 32 841	224 32 741

2x Xicato LED - 2x 7,4 W - 2x 720lm

☐ - 230V/50Hz - ☑ - ☐ - ☐ - ☐
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 115 mm (models beam angle 36°)
h = 150 mm (models beam angle 12° or 24°)

INDOX 2X50 MINI HAL


REF N° 224 10 051

☐ 2x QR-CBC 51 - 50W - Gx5.3 - 12V
☐ - ☑ - ☐ - ☐ - ☐ - ☐
h = 92 mm - exclusive lamp and transfo

INDOX 2X50 MINI ES

REF N° 224 11 051

☐ 2x QPAR 16 - 50W - GZ10/GU10 - ☐
☐ - ☑ - 230V/50Hz - ☐ - ☐ - ☐
h = 93 mm - exclusive lamp



INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 224 99 025 installation system for gypsum ceiling 25 mm

REF N° 224 99 030 installation system for gypsum ceiling 30 mm

BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI



INDOX 2X50 MINI IP54

OUTDOOR - ESTERNO - AUßENBEREICH - EXTERIEUR - EXTÉRIEUR - EXTERIOR

Fix (not adjustable) 0° - 0°

114x244 mm

Material : waterproof CALCYT+®

INDOX 2X50 MINI LED WARM-DIM	
WARMDIM : DIMS FROM 3000°K TO 2000°K	
REF N°	500LM CRI80
phase DIM	224 72 645
DIM 1-10V	224 62 645
DIM DALI	224 32 645
2x 6 W - 2x 500lm - 4 Step MacAdam ☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐ Incl. LED driver (phase DIM, 1-10V or DALI) Standard beam angle 36° (options 24°) h = 115 mm	


INDOX 2X50 MINI LED 1300LM CRI 80			
REF N°	2700°K	3000°K	4000°K
phase DIM	224 73 045	224 73 145	224 73 245
DIM 1-10V	224 63 045	224 63 145	224 63 245
DIM DALI	224 33 045	224 33 145	224 33 245
2x Xicato LED - 2x 11,7 W - 2x 1300lm ☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐ Incl. LED driver (phase DIM, 1-10V or DALI) Standard beam angle 36° (options 12°, 24°) h = 150 mm			

INDOX 2X50 MINI LED 700LM CRI 80			
REF N°	2700°K	3000°K	4000°K
phase DIM	224 72 045	224 72 145	224 72 245
DIM 1-10V	224 62 045	224 62 145	224 62 245
DIM DALI	224 32 045	224 32 145	224 32 245
2x Xicato LED - 2x 5,6 W - 2x 720lm ☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐ Incl. LED driver (phase DIM, 1-10V or DALI) Standard beam angle 36° (options 12°, 24°) h = 92 mm (phase DIM models beam 36°) h = 115 mm (all other models)			

INDOX 2X50 MINI LED 700LM CRI 97			
REF N°	2700°K	3000°K	4000°K
phase DIM	224 72 945	224 72 845	224 72 745
DIM 1-10V	224 62 945	224 62 845	224 62 745
DIM DALI	224 32 945	224 32 845	224 32 745
2x Xicato LED - 2x 7,4 W - 2x 720lm ☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐ Incl. LED driver (phase DIM, 1-10V or DALI) Standard beam angle 36° (options 12°, 24°) h = 115 mm (models beam angle 36°) h = 150 mm (models beam angle 12° or 24°)			

INDOX 2X50 MINI HAL	
REF N° 224 10 055	
☐ 2x QR-CBC 51 - 50W - Gx5.3 - 12V ☐ - ☐ - ☐ - ☐ - ☐ - ☐ h = 92 mm - exclusive lamp and transfo	

INDOX 2X50 MINI ES	
REF N° 224 11 055	
☐ 2x QPAR 16 - 50W - GZ10/GU10 - ☐ ☐ - ☐ - 230V/50Hz - ☐ - ☐ - ☐ h = 93 mm - exclusive lamp	



INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 224 99 025 installation system for gypsum ceiling 25 mm

REF N° 224 99 030 installation system for gypsum ceiling 30 mm

BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI



INDOX 50 IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable Φ 0° - 30°

144x168 mm

Material : CALCYT® plaster

INDOX 50 LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80	900LM CRI90
phase DIM	230 72 640	230 73 640
DIM 1-10V	230 62 640	230 63 640
DIM DALI	230 32 640	230 33 640

6W (500lm) - 12,8W (900lm) - 4 Step MacAdam
 - 230V/50Hz -  -  - 
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 24°)
 h = 120 mm (500lm) - h = 155 mm (900lm)

INDOX 50 LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	230 73 040	230 73 140	230 73 240
DIM 1-10V	230 63 040	230 63 140	230 63 240
DIM DALI	230 33 040	230 33 140	230 33 240

Xicato LED - 11,7W - 1300lm - 2 Step MacAdam
 - 230V/50Hz -  -  - 
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 155 mm

INDOX 50 LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	230 72 040	230 72 140	230 72 240
DIM 1-10V	230 62 040	230 62 140	230 62 240
DIM DALI	230 32 040	230 32 140	230 32 240

Xicato LED - 5,6 W - 720lm - 2 Step MacAdam
 - 230V/50Hz -  -  - 
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 98 mm (phase DIM models beam 36°)
 h = 120 mm (all other models)

INDOX 50 LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	230 72 940	230 72 840	230 72 740
DIM 1-10V	230 62 940	230 62 840	230 62 740
DIM DALI	230 32 940	230 32 840	230 32 740

Xicato LED - 7,4 W - 720lm - 2 Step MacAdam
 - 230V/50Hz -  -  - 
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 120 mm (models beam angle 36°)
 h = 155 mm (models beam angle 12° or 24°)

INDOX 50 HAL



REF N° 230 10 050

 QR-CBC 51 - 50W - Gx5.3 - 12V
 -  -  -  - 0.5m - 
 h = 98 mm - exclusive lamp and transfo

INDOX 50 ES

REF N° 230 11 050

 QPAR 16 - 50W - GZ10/GU10 - 
 -  - 230V/50Hz -  - 0.5m - 
 h = 100 mm - exclusive lamp




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 230 99 025 installation system for gypsum ceiling 25 mm

REF N° 230 99 030 installation system for gypsum ceiling 30 mm

REF N° 834 00 000 Concrete box Indox 50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI

INDOX 50 IP20

ACCESSORIES - ACCESSORI - ZUBEHÖR - ACCESSOIRES - ACCESORIOS



201



STANDARD (included) LAMPHOLDER RING WHITE



REF N° 201 10 002 LAMPHOLDER RING BLACK



REF N° 201 11 001
EXTENSION S WHITE
Ø 56 x 26 mm Φ 0° - 10°



REF N° 201 12 001
EXTENSION M WHITE
Ø 56 x 36 mm Φ 0° - 10°



REF N° 201 13 001
EXTENSION L WHITE
Ø 56 x 68 mm Φ 0° - 10°



REF N° 201 11 002
EXTENSION S BLACK
Ø 56 x 26 mm Φ 0° - 10°



REF N° 201 12 002
EXTENSION M BLACK
Ø 56 x 36 mm Φ 0° - 10°



REF N° 201 13 002
EXTENSION L BLACK
Ø 56 x 68 mm Φ 0° - 10°



REF N° 201 51 001
FROSTED PLEXI WHITE
Only for LED lampsources



REF N° 201 52 001
HONEYCOMB WHITE
Only for LED lampsources



REF N° 201 53 001
SPHERICAL GLASS LENS
IN WHITE RING



REF N° 201 51 002
FROSTED PLEXI BLACK
Only for LED lampsources



REF N° 201 52 002
HONEYCOMB BLACK
Only for LED lampsources



REF N° 201 53 002
SPHERICAL GLASS LENS
IN BLACK RING

INDOX 50 IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

144x168 mm

Material: CALCYT® plaster

INDOX 50 LED WARMDIM

WARMDIM: DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80	900LM CRI90
phase DIM	230 72 641	230 73 641
DIM 1-10V	230 62 641	230 63 641
DIM DALI	230 32 641	230 33 641

6W (500lm) - 12,8W (900lm) - 4 Step MacAdam

☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 24°)

h = 120 mm (500lm) - h = 155 mm (900lm)

INDOX 50 LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	230 73 041	230 73 141	230 73 241
DIM 1-10V	230 63 041	230 63 141	230 63 241
DIM DALI	230 33 041	230 33 141	230 33 241

Xicato LED - 11,7W - 1300lm - 2 Step MacAdam

☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 155 mm

INDOX 50 LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	230 72 041	230 72 141	230 72 241
DIM 1-10V	230 62 041	230 62 141	230 62 241
DIM DALI	230 32 041	230 32 141	230 32 241

Xicato LED - 5,6 W - 720lm - 2 Step MacAdam

☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 98 mm (phase DIM models beam 36°)

h = 120 mm (all other models)

INDOX 50 LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	230 72 941	230 72 841	230 72 741
DIM 1-10V	230 62 941	230 62 841	230 62 741
DIM DALI	230 32 941	230 32 841	230 32 741

Xicato LED - 7,4 W - 720lm - 2 Step MacAdam

☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 120 mm (models beam angle 36°)

h = 155 mm (models beam angle 12° or 24°)

INDOX 50 HAL

REF N° 230 10 051

☐ QR-CBC 51 - 50W - Gx5.3 - 12V

☐ - ☐ - ☐ - ☐ - ☐ - ☐ - ☐

h = 98 mm - exclusive lamp and transfo




INDOX 50 ES

REF N° 230 11 051

☐ QPAR 16 - 50W - GZ10/GU10 - ☐

☐ - ☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐

h = 100 mm - exclusive lamp




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 230 99 025 installation system for gypsum ceiling 25 mm

REF N° 230 99 030 installation system for gypsum ceiling 30 mm

REF N° 834 00 000 Concrete box Indox 50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI



INDOX 50 IP54

OUTDOOR - ESTERNO - AUßENBEREICH - EXTERIEUR - EXTERIOR

Fix (not adjustable) 0° - 0°

144x168 mm

Material : waterproof CALCYT+*

INDOX 50 LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80	900LM CRI90
phase DIM	230 72 645	230 73 645
DIM 1-10V	230 62 645	230 63 645
DIM DALI	230 32 645	230 33 645

6W (500lm) - 12,8W (900lm) - 4 Step MacAdam

☐ - 230V/50Hz - CE - ▽ - A - B

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 24°)

h = 120 mm (500lm) - h = 155 mm (900lm)

INDOX 50 LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	230 73 045	230 73 145	230 73 245
DIM 1-10V	230 63 045	230 63 145	230 63 245
DIM DALI	230 33 045	230 33 145	230 33 245

Xicato LED - 11,7W - 1300lm - 2 Step MacAdam

☐ - 230V/50Hz - CE - ▽ - A - A

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 155 mm

INDOX 50 LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	230 72 045	230 72 145	230 72 245
DIM 1-10V	230 62 045	230 62 145	230 62 245
DIM DALI	230 32 045	230 32 145	230 32 245

Xicato LED - 5,6 W - 720lm - 2 Step MacAdam

☐ - 230V/50Hz - CE - ▽ - A - A

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 98 mm (phase DIM models beam 36°)

h = 120 mm (all other models)

INDOX 50 LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	230 72 945	230 72 845	230 72 745
DIM 1-10V	230 62 945	230 62 845	230 62 745
DIM DALI	230 32 945	230 32 845	230 32 745

Xicato LED - 7,4 W - 720lm - 2 Step MacAdam

☐ - 230V/50Hz - CE - ▽ - A - A

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 120 mm (models beam angle 36°)

h = 155 mm (models beam angle 12° or 24°)

INDOX 50 HAL

REF N° 230 10 055

☐ QR-CBC 51 - 50W - Gx5.3 - 12V

☐ - CE - ▽ - 0.5m - D

h = 98 mm - exclusive lamp and transfo



INDOX 50 ES

REF N° 230 11 055

☐ QPAR 16 - 50W - GZ10/GU10 - A

☐ - CE - 230V/50Hz - ▽ - 0.5m - D

h = 100 mm - exclusive lamp




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 230 99 025 installation system for gypsum ceiling 25 mm

REF N° 230 99 030 installation system for gypsum ceiling 30 mm

REF N° 834 00 000 Concrete box Indox 50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI



INDOX 50 W IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable ϕ 0° - 30°

144x168 mm

Material : CALCYT® plaster

INDOX 50 W LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80	900LM CRI90
phase DIM	222 72 640	222 73 640
DIM 1-10V	222 62 640	222 63 640
DIM DALI	222 32 640	222 33 640

6W (500lm) - 12,8W (900lm) - 4 Step MacAdam
 $\square$ - 230V/50Hz - CE - ∇ - A - B
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 24°)
 h = 120 mm (500lm) - h = 155 mm (900lm)

INDOX 50 W LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	222 73 040	222 73 140	222 73 240
DIM 1-10V	222 63 040	222 63 140	222 63 240
DIM DALI	222 33 040	222 33 140	222 33 240

Xicato LED - 11,7W - 1300lm - 2 Step MacAdam
 $\square$ - 230V/50Hz - CE - ∇ - A - A
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 155 mm

INDOX 50 W LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	222 72 040	222 72 140	222 72 240
DIM 1-10V	222 62 040	222 62 140	222 62 240
DIM DALI	222 32 040	222 32 140	222 32 240

Xicato LED - 5,6 W - 720lm - 2 Step MacAdam
 $\square$ - 230V/50Hz - CE - ∇ - A - A^+
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 98 mm (phase DIM models beam 36°)
 h = 120 mm (all other models)

INDOX 50 W LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	222 72 940	222 72 840	222 72 740
DIM 1-10V	222 62 940	222 62 840	222 62 740
DIM DALI	222 32 940	222 32 840	222 32 740

Xicato LED - 7,4 W - 720lm - 2 Step MacAdam
 $\square$ - 230V/50Hz - CE - ∇ - A - A
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 120 mm (models beam angle 36°)
 h = 155 mm (models beam angle 12° or 24°)

INDOX 50 W HAL





REF N° 222 10 050

$\square$ QR-CBC 51 - 50W - Gx5.3 - 12V
 $\diamond$ - CE - A - ∇ - D - D
 h = 98 mm - exclusive lamp and transfo

INDOX 50 W ES

REF N° 222 11 050

$\square$ QPAR 16 - 50W - GZ10/GU10 - A
 $\diamond$ - CE - 230V/50Hz - ∇ - D - D
 h = 100 mm - exclusive lamp



INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 222 99 025 installation system for gypsum ceiling 25 mm

REF N° 222 99 030 installation system for gypsum ceiling 30 mm

BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI

INDOX 50 W IP20

ACCESSORIES - ACCESSORI - ZUBEHÖR - ACCESSOIRES - ACCESORIOS



207



STANDARD (included) LAMPHOLDER RING WHITE



REF N° 201 10 002 LAMPHOLDER RING BLACK



REF N° 201 11 001
EXTENSION S WHITE
Ø 56 x 26 mm $\angle$ 0° - 10°



REF N° 201 12 001
EXTENSION M WHITE
Ø 56 x 36 mm $\angle$ 0° - 10°



REF N° 201 13 001
EXTENSION L WHITE
Ø 56 x 68 mm $\angle$ 0° - 10°



REF N° 201 11 002
EXTENSION S BLACK
Ø 56 x 26 mm $\angle$ 0° - 10°



REF N° 201 12 002
EXTENSION M BLACK
Ø 56 x 36 mm $\angle$ 0° - 10°



REF N° 201 13 002
EXTENSION L BLACK
Ø 56 x 68 mm $\angle$ 0° - 10°



REF N° 201 51 001
FROSTED PLEXI WHITE
Only for LED lampsources



REF N° 201 52 001
HONEYCOMB WHITE
Only for LED lampsources



REF N° 201 53 001
SPHERICAL GLASS LENS
IN WHITE RING



REF N° 201 51 002
FROSTED PLEXI BLACK
Only for LED lampsources



REF N° 201 52 002
HONEYCOMB BLACK
Only for LED lampsources



REF N° 201 53 002
SPHERICAL GLASS LENS
IN BLACK RING

INDOX 50 W IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

144x168 mm

Material: CALCYT® plaster

INDOX 50 W LED WARMDIM

WARMDIM: DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80	900LM CRI90
phase DIM	222 72 641	222 73 641
DIM 1-10V	222 62 641	222 63 641
DIM DALI	222 32 641	222 33 641

6W (500lm) - 12,8W (900lm) - 4 Step MacAdam

☐ - 230V/50Hz - ☑ - ☐ - ☐ - ☐

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 24°)

h = 120 mm (500lm) - h = 155 mm (900lm)

INDOX 50 W LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	222 73 041	222 73 141	222 73 241
DIM 1-10V	222 63 041	222 63 141	222 63 241
DIM DALI	222 33 041	222 33 141	222 33 241

Xicato LED - 11,7W - 1300lm - 2 Step MacAdam

☐ - 230V/50Hz - ☑ - ☐ - ☐ - ☐

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 155 mm

INDOX 50 W LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	222 72 041	222 72 141	222 72 241
DIM 1-10V	222 62 041	222 62 141	222 62 241
DIM DALI	222 32 041	222 32 141	222 32 241

Xicato LED - 5,6 W - 720lm - 2 Step MacAdam

☐ - 230V/50Hz - ☑ - ☐ - ☐ - ☐

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 98 mm (phase DIM models beam 36°)

h = 120 mm (all other models)

INDOX 50 W LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	222 72 941	222 72 841	222 72 741
DIM 1-10V	222 62 941	222 62 841	222 62 741
DIM DALI	222 32 941	222 32 841	222 32 741

Xicato LED - 7,4 W - 720lm - 2 Step MacAdam

☐ - 230V/50Hz - ☑ - ☐ - ☐ - ☐

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 120 mm (models beam angle 36°)

h = 155 mm (models beam angle 12° or 24°)

INDOX 50 W HAL

REF N° 222 10 051

☐ QR-CBC 51 - 50W - Gx5.3 - 12V

☐ - ☑ - ☐ - ☐ - ☐ - ☐ - ☐

h = 98 mm - exclusive lamp and transfo




INDOX 50 W ES

REF N° 222 11 051

☐ QPAR 16 - 50W - GZ10/GU10 - ☐

☐ - ☑ - 230V/50Hz - ☐ - ☐ - ☐ - ☐

h = 100 mm - exclusive lamp



INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 222 99 025 installation system for gypsum ceiling 25 mm

REF N° 222 99 030 installation system for gypsum ceiling 30 mm

BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°


EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI



INDOX 50 W IP54

OUTDOOR - ESTERNO - AUßENBEREICH - EXTERIEUR - EXTERIOR

Fix (not adjustable) 0° - 0°

144x168 mm

Material : waterproof CALCYT+*

INDOX 50 W LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80	900LM CRI90
phase DIM	222 72 645	222 73 645
DIM 1-10V	222 62 645	222 63 645
DIM DALI	222 32 645	222 33 645

6W (500lm) - 12,8W (900lm) - 4 Step MacAdam
 □ - 230V/50Hz - - -
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 24°)
 h = 120 mm (500lm) - h = 155 mm (900lm)

INDOX 50 W LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	222 73 045	222 73 145	222 73 245
DIM 1-10V	222 63 045	222 63 145	222 63 245
DIM DALI	222 33 045	222 33 145	222 33 245

Xicato LED - 11,7W - 1300lm - 2 Step MacAdam
 □ - 230V/50Hz - - -
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 155 mm

INDOX 50 W LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	222 72 045	222 72 145	222 72 245
DIM 1-10V	222 62 045	222 62 145	222 62 245
DIM DALI	222 32 045	222 32 145	222 32 245

Xicato LED - 5,6 W - 720lm - 2 Step MacAdam
 □ - 230V/50Hz - - -
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 98 mm (phase DIM models beam 36°)
 h = 120 mm (all other models)

INDOX 50 W LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	222 72 945	222 72 845	222 72 745
DIM 1-10V	222 62 945	222 62 845	222 62 745
DIM DALI	222 32 945	222 32 845	222 32 745

Xicato LED - 7,4 W - 720lm - 2 Step MacAdam
 □ - 230V/50Hz - - -
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 120 mm (models beam angle 36°)
 h = 155 mm (models beam angle 12° or 24°)

INDOX 50 W HAL




REF N° 222 10 055

QR-CBC 51 - 50W - Gx5.3 - 12V
 - - -
 h = 98 mm - exclusive lamp and transfo

INDOX 50 W ES

REF N° 222 11 055

QPAR 16 - 50W - GZ10/GU10 - - -
 h = 100 mm - exclusive lamp



INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 222 99 025 installation system for gypsum ceiling 25 mm

REF N° 222 99 030 installation system for gypsum ceiling 30 mm

BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI



INDOX 2X50 IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable Φ 0° - 30°

144x283 mm

Material : CALCYT® plaster

INDOX 2X50 LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80
phase DIM	229 72 640
DIM 1-10V	229 62 640
DIM DALI	229 32 640

2x 6 W - 2x 500lm - 4 Step MacAdam

☐ - 230V/50Hz - - -

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 24°)

h = 120 mm

INDOX 2X50 LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	229 73 040	229 73 140	229 73 240
DIM 1-10V	229 63 040	229 63 140	229 63 240
DIM DALI	229 33 040	229 33 140	229 33 240

2x Xicato LED - 2x 11,7 W - 2x 1300lm

☐ - 230V/50Hz - - -

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 155 mm

INDOX 2X50 LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	229 72 040	229 72 140	229 72 240
DIM 1-10V	229 62 040	229 62 140	229 62 240
DIM DALI	229 32 040	229 32 140	229 32 240

2x Xicato LED - 2x 5,6 W - 2x 720lm

☐ - 230V/50Hz - - -

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 98 mm (phase DIM models beam 36°)

h = 120 mm (all other models)

INDOX 2X50 LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	229 72 940	229 72 840	229 72 740
DIM 1-10V	229 62 940	229 62 840	229 62 740
DIM DALI	229 32 940	229 32 840	229 32 740

2x Xicato LED - 2x 7,4 W - 2x 720lm

☐ - 230V/50Hz - - -

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 120 mm (models beam angle 36°)

h = 155 mm (models beam angle 12° or 24°)

INDOX 2X50 HAL

REF N° 229 10 050

☐ 2x QR-CBC 51 - 50W - Gx5.3 - 12V

☐ - - - -

h = 98 mm - exclusive lamp and transfo



INDOX 2X50 ES

REF N° 229 11 050

☐ 2x QPAR 16 - 50W - GZ10/GU10 -

☐ - - 230V/50Hz - - -

h = 100 mm - exclusive lamp




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 229 99 025 installation system for gypsum ceiling 25 mm

REF N° 229 99 030 installation system for gypsum ceiling 30 mm

REF N° 829 00 000 Concrete box Indox 2x50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI

INDOX 2X50 IP20

ACCESSORIES - ACCESSORI - ZUBEHÖR - ACCESSOIRES - ACCESORIOS



STANDARD (included) 2 x LAMPHOLDER RING WHITE



REF N° 201 10 022 2 x LAMPHOLDER RING BLACK



REF N° 201 11 001
1 x EXTENSION S WHITE
Ø 56 x 26 mm $\odot$ 0° - 10°



REF N° 201 12 001
1 x EXTENSION M WHITE
Ø 56 x 36 mm $\odot$ 0° - 10°



REF N° 201 13 001
1 x EXTENSION L WHITE
Ø 56 x 68 mm $\odot$ 0° - 10°



REF N° 201 11 002
1 x EXTENSION S BLACK
Ø 56 x 26 mm $\odot$ 0° - 10°



REF N° 201 12 002
1 x EXTENSION M BLACK
Ø 56 x 36 mm $\odot$ 0° - 10°



REF N° 201 13 002
1 x EXTENSION L BLACK
Ø 56 x 68 mm $\odot$ 0° - 10°



REF N° 201 51 001
1 x FROSTED PLEXI WHITE
Only for LED lampsources




REF N° 201 52 001
1 x HONEYCOMB WHITE
Only for LED lampsources



REF N° 201 53 001
1 x SPHERICAL GLASS LENS
IN WHITE RING



REF N° 201 51 002
1 x FROSTED PLEXI BLACK
Only for LED lampsources



REF N° 201 52 002
1 x HONEYCOMB BLACK
Only for LED lampsources



REF N° 201 53 002
1 x SPHERICAL GLASS LENS
IN BLACK RING

INDOX 2X50 IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

144x283 mm

Material : CALCYT® plaster

INDOX 2X50 LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80
phase DIM	229 72 641
DIM 1-10V	229 62 641
DIM DALI	229 32 641

2x 6 W - 2x 500lm - 4 Step MacAdam
 ☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 24°)
 h = 120 mm

INDOX 2X50 LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	229 73 041	229 73 141	229 73 241
DIM 1-10V	229 63 041	229 63 141	229 63 241
DIM DALI	229 33 041	229 33 141	229 33 241

2x Xicato LED - 2x 11,7 W - 2x 1300lm
 ☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 155 mm

INDOX 2X50 LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	229 72 041	229 72 141	229 72 241
DIM 1-10V	229 62 041	229 62 141	229 62 241
DIM DALI	229 32 041	229 32 141	229 32 241

2x Xicato LED - 2x 5,6 W - 2x 720lm
 ☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 98 mm (phase DIM models beam 36°)
 h = 120 mm (all other models)

INDOX 2X50 LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	229 72 941	229 72 841	229 72 741
DIM 1-10V	229 62 941	229 62 841	229 62 741
DIM DALI	229 32 941	229 32 841	229 32 741

2x Xicato LED - 2x 7,4 W - 2x 720lm
 ☐ - 230V/50Hz - ☐ - ☐ - ☐ - ☐
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 120 mm (models beam angle 36°)
 h = 155 mm (models beam angle 12° or 24°)

INDOX 2X50 HAL



REF N° 229 10 051

☐ 2x QR-CBC 51 - 50W - Gx53 - 12V
 ☐ - ☐ - ☐ - ☐ - ☐ - ☐
 h = 98 mm - exclusive lamp and transfo

INDOX 2X50 ES

REF N° 229 11 051

☐ 2x QPAR 16 - 50W - GZ10/GU10 - ☐
 ☐ - ☐ - 230V/50Hz - ☐ - ☐ - ☐
 h = 100 mm - exclusive lamp




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 229 99 025 installation system for gypsum ceiling 25 mm

REF N° 229 99 030 installation system for gypsum ceiling 30 mm

REF N° 829 00 000 Concrete box Indox 2x50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI





INDOX 3X50 IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTERIOR

Adjustable Φ 0° - 30°

168x359 mm

Material : CALCYT® plaster

INDOX 3X50 LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80
phase DIM	223 72 640
DIM 1-10V	223 62 640
DIM DALI	223 32 640

3x 6 W - 3x 500lm - 4 Step MacAdam

☐ - 230V/50Hz - - - -
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 24°)
h = 120 mm

INDOX 3X50 LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	223 73 040	223 73 140	223 73 240
DIM 1-10V	223 63 040	223 63 140	223 63 240
DIM DALI	223 33 040	223 33 140	223 33 240

3x Xicato LED - 3x 11,7 W - 3x 1300lm

☐ - 230V/50Hz - - - -
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 155 mm

INDOX 3X50 LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	223 72 040	223 72 140	223 72 240
DIM 1-10V	223 62 040	223 62 140	223 62 240
DIM DALI	223 32 040	223 32 140	223 32 240

3x Xicato LED - 3x 5,6 W - 3x 720lm

☐ - 230V/50Hz - - - -
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 98 mm (phase DIM models beam 36°)
h = 120 mm (all other models)

INDOX 3X50 LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	223 72 940	223 72 840	223 72 740
DIM 1-10V	223 62 940	223 62 840	223 62 740
DIM DALI	223 32 940	223 32 840	223 32 740

3x Xicato LED - 3x 7,4 W - 3x 720lm

☐ - 230V/50Hz - - - -
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 120 mm (models beam angle 36°)
h = 155 mm (models beam angle 12° or 24°)

INDOX 3X50 HAL



REF N° 223 10 050

3x QR-CBC 51 - 50W - Gx53 - 12V
 - - - -
h = 98 mm - exclusive lamp and transfo

INDOX 3X50 ES

REF N° 223 11 050

3x QPAR 16 - 50W - GZ10/GU10 -
 - 230V/50Hz - - -
h = 100 mm - exclusive lamp




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 223 99 025 installation system for gypsum ceiling 25 mm

REF N° 223 99 030 installation system for gypsum ceiling 30 mm

REF N° 844 00 000 Concrete box Indox 3x50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI

INDOX 3X50 IP20

ACCESSORIES - ACCESSORI - ZUBEHÖR - ACCESSOIRES - ACCESORIOS



STANDARD (included) 3 x LAMPHOLDER RING WHITE



REF N° 201 10 032 3 x LAMPHOLDER RING BLACK



REF N° 201 11 001
1 x EXTENSION S WHITE
Ø 56 x 26 mm $\angle$ 0° - 10°



REF N° 201 12 001
1 x EXTENSION M WHITE
Ø 56 x 36 mm $\angle$ 0° - 10°



REF N° 201 13 001
1 x EXTENSION L WHITE
Ø 56 x 68 mm $\angle$ 0° - 10°



REF N° 201 11 002
1 x EXTENSION S BLACK
Ø 56 x 26 mm $\angle$ 0° - 10°



REF N° 201 12 002
1 x EXTENSION M BLACK
Ø 56 x 36 mm $\angle$ 0° - 10°



REF N° 201 13 002
1 x EXTENSION L BLACK
Ø 56 x 68 mm $\angle$ 0° - 10°



REF N° 201 51 001
1 x FROSTED PLEXI WHITE
Only for LED lampsources




REF N° 201 52 001
1 x HONEYCOMB WHITE
Only for LED lampsources



REF N° 201 53 001
1 x SPHERICAL GLASS LENS
IN WHITE RING



REF N° 201 51 002
1 x FROSTED PLEXI BLACK
Only for LED lampsources



REF N° 201 52 002
1 x HONEYCOMB BLACK
Only for LED lampsources



REF N° 201 53 002
1 x SPHERICAL GLASS LENS
IN BLACK RING

INDOX 3X50 IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

168x359 mm

Material : CALCYT® plaster

INDOX 3X50 LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80
phase DIM	223 72 641
DIM 1-10V	223 62 641
DIM DALI	223 32 641

3x 6 W - 3x 500lm - 4 Step MacAdam

☐ - 230V/50Hz - - -
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 24°)
h = 120 mm

INDOX 3X50 LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	223 73 041	223 73 141	223 73 241
DIM 1-10V	223 63 041	223 63 141	223 63 241
DIM DALI	223 33 041	223 33 141	223 33 241

3x Xicato LED - 3x 11,7 W - 3x 1300lm

☐ - 230V/50Hz - - -
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 155 mm

INDOX 3X50 LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	223 72 041	223 72 141	223 72 241
DIM 1-10V	223 62 041	223 62 141	223 62 241
DIM DALI	223 32 041	223 32 141	223 32 241

3x Xicato LED - 3x 5,6 W - 3x 720lm

☐ - 230V/50Hz - - -
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 98 mm (phase DIM models beam 36°)
h = 120 mm (all other models)

INDOX 3X50 LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	223 72 941	223 72 841	223 72 741
DIM 1-10V	223 62 941	223 62 841	223 62 741
DIM DALI	223 32 941	223 32 841	223 32 741

3x Xicato LED - 3x 7,4 W - 3x 720lm

☐ - 230V/50Hz - - -
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 120 mm (models beam angle 36°)
h = 155 mm (models beam angle 12° or 24°)

INDOX 3X50 HAL


REF N° 223 10 051

☐ 3x QR-CBC 51 - 50W - Gx5.3 - 12V
 - - - -
h = 98 mm - exclusive lamp and transfo

INDOX 3X50 ES

REF N° 223 11 051

☐ 3x QPAR 16 - 50W - GZ10/GU10 -
 - 230V/50Hz - - -
h = 100 mm - exclusive lamp




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 223 99 025 installation system for gypsum ceiling 25 mm

REF N° 223 99 030 installation system for gypsum ceiling 30 mm

REF N° 844 00 000 Concrete box Indox 3x50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI



INDOX 3X50 IP54

OUTDOOR - ESTERNO - AUßENBEREICH - EXTERIEUR - EXTERIOR

Fix (not adjustable) 0° - 0°

168x359 mm

Material : waterproof CALCYT+®

INDOX 3X50 LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80
phase DIM	223 72 645
DIM 1-10V	223 62 645
DIM DALI	223 32 645

3x 6 W - 3x 500lm - 4 Step MacAdam

☐ - 230V/50Hz - CE - ▽ - ⚡ - B

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 24°)

h = 120 mm

INDOX 3X50 LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	223 73 045	223 73 145	223 73 245
DIM 1-10V	223 63 045	223 63 145	223 63 245
DIM DALI	223 33 045	223 33 145	223 33 245

3x Xicato LED - 3x 11,7 W - 3x 1300lm

☐ - 230V/50Hz - CE - ▽ - ⚡ - A

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 155 mm

INDOX 3X50 LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	223 72 045	223 72 145	223 72 245
DIM 1-10V	223 62 045	223 62 145	223 62 245
DIM DALI	223 32 045	223 32 145	223 32 245

3x Xicato LED - 3x 5,6 W - 3x 720lm

☐ - 230V/50Hz - CE - ▽ - ⚡ - A

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 98 mm (phase DIM models beam 36°)

h = 120 mm (all other models)

INDOX 3X50 LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	223 72 945	223 72 845	223 72 745
DIM 1-10V	223 62 945	223 62 845	223 62 745
DIM DALI	223 32 945	223 32 845	223 32 745

3x Xicato LED - 3x 7,4 W - 3x 720lm

☐ - 230V/50Hz - CE - ▽ - ⚡ - A

Incl. LED driver (phase DIM, 1-10V or DALI)

Standard beam angle 36° (options 12°, 24°)

h = 120 mm (models beam angle 36°)

h = 155 mm (models beam angle 12° or 24°)

INDOX 3X50 HAL

REF N° 223 10 055

☎ 3x QR-CBC 51 - 50W - Gx5.3 - 12V

☐ - CE - ⚡ - ▽ - 0.5m - D

h = 98 mm - exclusive lamp and transfo



INDOX 3X50 ES

REF N° 223 11 055

☎ 3x QPAR 16 - 50W - GZ10/GU10 - ⚡

☐ - CE - 230V/50Hz - ▽ - 0.5m - D

h = 100 mm - exclusive lamp




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 223 99 025 installation system for gypsum ceiling 25 mm

REF N° 223 99 030 installation system for gypsum ceiling 30 mm

REF N° 844 00 000 Concrete box Indox 3x50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI



INDOX 111 IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable $\odot$ 0° - 30°

$\square$ 194x218 mm

Material : CALCYT® plaster

INDOX 111 LED 3000LM CRI 80

REF N°	2700°K	3000°K	4000°K
on/off	231 26 040	231 26 140	231 26 240
DIM 1-10V	231 66 040	231 66 140	231 66 240
DIM DALI	231 36 040	231 36 140	231 36 240

Xicato LED - 29,3 W - 3000lm - 2 Step MacAdam
 $\square$ - 230V/50Hz - CE - ∇ - A
 Beam angle 36° (option 20°) - Incl LED driver
 h = 161 mm

INDOX 111 LED 2000LM CRI 80

REF N°	2700°K	3000°K	4000°K
on/off	231 25 040	231 25 140	231 25 240
phase DIM	231 75 040	231 75 140	231 75 240
DIM 1-10V	231 65 040	231 65 140	231 65 240
DIM DALI	231 35 040	231 35 140	231 35 240

Xicato LED - 19,5 W - 2000lm - 2 Step MacAdam
 $\square$ - 230V/50Hz - CE - ∇ - A
 Beam 36° (option 20°) - Incl LED driver
 h = 161 mm

INDOX 111 LED 1300LM CRI 97

REF N°	2700°K	3000°K	4000°K
on/off	231 23 940	231 23 840	231 23 740
phase DIM	231 73 940	231 73 840	231 73 740
DIM 1-10V	231 63 940	231 63 840	231 63 740
DIM DALI	231 33 940	231 33 840	231 33 740

Xicato LED - 17,6 W - 1300lm - 2 Step MacAdam
 $\square$ - 230V/50Hz - CE - ∇ - A
 Beam angle 36° (option 20°) - Incl LED driver
 h = 161 mm

INDOX 111 LED 2000LM CRI 97

REF N°	2700°K	3000°K	4000°K
on/off	231 25 940	231 25 840	231 25 740
phase DIM	231 75 940	231 75 840	231 75 740
DIM 1-10V	231 65 940	231 65 840	231 65 740
DIM DALI	231 35 940	231 35 840	231 35 740

Xicato LED - 22,3 W - 2000lm - 2 Step MacAdam
 $\square$ - 230V/50Hz - CE - ∇ - A
 Beam angle 36° (option 20°) - Incl LED driver
 h = 161 mm

INDOX 111 AR

REF N° 231 13 100




QR-LP 111 - 100W - G53 - 12V - CE - D
 excl. transfo - ∇ - D - CE - D
 h = 116 mm

INDOX 111 CDM

REF N° 231 19 070 CDM-TC - G8.5

REF N° 231 12 070 CDM-R - GX8.5

35W or 70W - 230V/50Hz - CE - B
 h = 154 mm - ∇ - D - CE - B




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 231 99 025 installation system for gypsum ceiling 25 mm

REF N° 231 99 030 installation system for gypsum ceiling 30 mm

REF N° 831 00 000 Concrete box Indox 111 - Galvanized steel



BEAM ANGLES & OPTIONS

STANDARD (included) beam angle 36°

REF N° 205 11 020 optional beam angle 20°

REF N° 201 00 060 Frosted diffuser for 111 LED series

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI





INDOX 2X111 IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable Φ 0° - 30°

194x408 mm

Material : CALCYT® plaster




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 232 99 025 installation system for gypsum ceiling 25 mm

REF N° 232 99 030 installation system for gypsum ceiling 30 mm

REF N° 832 00 000 Concrete box Indox 2x111 - Galvanized steel



BEAM ANGLES & OPTIONS

STANDARD (included) beam angle 36°

REF N° 205 11 020 optional beam angle 20°

REF N° 201 00 060 Frosted diffuser for 111 LED series

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI

INDOX 2X111 LED 3000LM CRI 80

REF N°	2700°K	3000°K	4000°K
on/off	232 26 040	232 26 140	232 26 240
DIM 1-10V	232 66 040	232 66 140	232 66 240
DIM DALI	232 36 040	232 36 140	232 36 240

2x Xicato LED - 2x 29,3 W - 2x 3000lm

□ - 230V/50Hz - - - - - -

Beam angle 36° (option 20°) - Incl LED driver
h = 161 mm

INDOX 2X111 LED 2000LM CRI 80

REF N°	2700°K	3000°K	4000°K
on/off	232 25 040	232 25 140	232 25 240
phase DIM	232 75 040	232 75 140	232 75 240
DIM 1-10V	232 65 040	232 65 140	232 65 240
DIM DALI	232 35 040	232 35 140	232 35 240

2x Xicato LED - 2x 19,5 W - 2x 2000lm

□ - 230V/50Hz - - - - - -

Beam 36° (option 20°) - Incl LED driver
h = 161 mm

INDOX 2X111 LED 1300LM CRI 97

REF N°	2700°K	3000°K	4000°K
on/off	232 23 940	232 23 840	232 23 740
phase DIM	232 73 940	232 73 840	232 73 740
DIM 1-10V	232 63 940	232 63 840	232 63 740
DIM DALI	232 33 940	232 33 840	232 33 740

2x Xicato LED - 2x 17,6 W - 2x 1300lm

□ - 230V/50Hz - - - - - -

Beam angle 36° (option 20°) - Incl LED driver
h = 161 mm

INDOX 2X111 LED 2000LM CRI 97

REF N°	2700°K	3000°K	4000°K
on/off	232 25 940	232 25 840	232 25 740
phase DIM	232 75 940	232 75 840	232 75 740
DIM 1-10V	232 65 940	232 65 840	232 65 740
DIM DALI	232 35 940	232 35 840	232 35 740


2x Xicato LED - 2x 22,3 W - 2x 2000lm

□ - 230V/50Hz - - - - - -

Beam angle 36° (option 20°) - Incl LED driver
h = 161 mm

INDOX 2X111 AR

REF N° 232 13 100



2x QR-LP 111 - 100W - G53 - 12V -

excl. transfo - - - - - -

h = 116 mm

INDOX 2X111 CDM

REF N° 232 19 070 CDM-TC - G8.5

REF N° 232 12 070 CDM-R - GX8.5

2x 35W or 2x 70W - 230V/50Hz -

h = 154 mm - - - - - -




INDOX 1434 IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Fix (not adjustable) 0° - 0°

191x474 mm

Material : CALCYT® plaster + frosted diffuser



INDOX 1434 TCL

REF N° 235 22 048

2x TC-L 24W
2G11 - 230V/50Hz - incl EVG
191x474 mm - 0.5m - IP40 - 850°C - eco

INDOX 1434 LED 2500LM

REF N° 235 25 000 on/off 2700K

REF N° 235 25 100 on/off 3000K

REF N° 235 65 000 DIM 1-10V 2700K

REF N° 235 65 100 DIM 1-10V 3000K

REF N° 235 35 000 DIM DALI 2700K

REF N° 235 35 100 DIM DALI 3000K

2550lm@ 70°C - 32W - 230V/50Hz - incl LED driver
191x474 mm - 0.5m - IP40 - 850°C - eco

INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 235 99 025 installation system for gypsum ceiling 25 mm

REF N° 235 99 030 installation system for gypsum ceiling 30 mm

REF N° 835 00 000 Concrete box Indox 1434 - Galvanized steel

